

FREE 在庫 2018年6月29日時点



NO	分類	メーカー	型番	数量	スペック
1	CHIP LED	BULLWILL	BW-320WW-DT	1,405	3.0 *2.0*1.3白 TOP VIEW
2	CHIP LED	BULLWILL	BW-192WT	140	1.6*0.8*0.4 白 TOP VIEW
3	CHIP LED	BULLWILL	BW-108URO (660nm)	80	2.8*1.2*0.8 赤 SIDE VIEW 635nm
4	CHIP LED	BULLWILL	BW-191URO	210	1.6*0.8*0.6 赤 TOP VIEW 635nm
5	CHIP LED	BULLWILL	BW-191UY	1,458	1.6*0.8*0.6黄色 TOP VIEW 595nm
6	DIP LED	STANLY	MPG3338S	200	3φ 緑 DIFFUSED 567nm
7	DIP LED	King Bright	WP3A8ID	8	3φ 赤 DIFFUSED 625nm
8	DIP LED	King Bright	WP3A8GD	20	3φ 緑 DIFFUSED 568nm
9	DIP LED	LIGITEK	LHRFSBK2092	500	3φ DUAL COLOR RED
10	SOCKET	ANDON	R375-SP16-02T-75S-R27-L14	50	16PIN THRU-HOLE 0.18φ in
11	CRYSTAL	EPSON	SG-8002JC24MHZPCB	30	OSCILLATOR 10.5×5.8×2.7mm SOJ4pin 24MHZ 3V ±50ppm -20~70°C
12	CRYSTAL	EPSON	SG-8002JC16MHZPCB	29	OSCILLATOR 10.5×5.8×2.7mm SOJ4pin 16MHZ 3V ±50ppm -20~70°C
13	CRYSTAL	FOX	FXO-HC536R-26.666	7	OSCILLATOR 5×3.2×1.4mm SOJ4pin 26.666MHZ 3.3V ±25ppm -40~85°C
14	CRYSTAL	SII	SSP-T7F 32.768KHZ±20PPM7PF	1,510	QUARTZ CRYSTAL 7×1.5×1.4mm 32.768KHZ ±20ppm
15	CRYSTAL	SII	VT-200-F(32.768KHZ ±20ppm 12.5pf)	191	QUARTZ CRYSTAL 2φ×6mm 32.768KHZ ±20ppm
16	CERAMIC CAPACITOR	SAMSUNG	CL21B105KAFNNNE	5,737	1μF 25V X7R 0805 (2012メートル法)
17	CERAMIC CAPACITOR	SAMSUNG	CL32A106KLULNNE	619	10μF 35V X5R 1210 (3225メートル法)
18	CERAMIC CAPACITOR	SAMSUNG	CL05B472KB5NNNC	7,887	4700PF 50V X7R 0402 (1005メートル法)
19	CERAMIC CAPACITOR	SAMSUNG	CL21B104JBCNNNC	3,280	0.1μF 50V X7R 0805 (2012メートル法)
20	CERAMIC CAPACITOR	SAMSUNG	CL21B103JBANNNC	3,695	0.01μF=10000PF 50V X7R 0805 (2012メートル法)
21	CERAMIC CAPACITOR	SAMSUNG	CL10F105ZO8NNNC	3,792	1μF 16V Y5V 0603 (1608メートル法)
22	CERAMIC CAPACITOR	MURATA	GRM188B11A105KA61D	1,977	1μF 10V B 0603 (1608メートル法)
23	CERAMIC CAPACITOR	MARUWA	HE40SJSL200J(20pf 50V)	1,000	DIP 20pf 50V
24	CERAMIC CAPACITOR	MARUWA	HE40SJYB121K(120pf 50v)	1,400	DIP 120pf 50V
25	CERAMIC CAPACITOR	MARUWA	HE40SJSL100D(10pf 50V)	800	DIP 10pf 50V

26	CERAMIC CAPACITOR	MARUWA	HE40SJYB221K(220pf 50V)	1,400	DIP 220pf 50V
27	CERAMIC CAPACITOR	MARUWA	SLU4100J5	4,000	SL特製 CLASS1 50V 4φ 10pf
28	CERAMIC CAPACITOR	MARUWA	SLU5151J6	4,000	SL特製 CLASS1 50V 5φ 150pf
29	IC	MICROCHIP	MCP9701T-E/TT	6,000	Temperature Sensor Analog, Local -10° C ~ 125° C 19.5mV/° C SOT-23-3
30	IC	ABLIC	S-93C66BD0I-J8T1G	1,200	EEPROM 3WIRE 4K ROM SOP8 PIN
31	IC	RENESAS	UPD78F1145AGB-GAH-AX	80	78系FAMILY 16BIT 64KB FLASH 64LQFP
32	IC	RENESAS	HVC202ATRU-E	4,000	Variable Capacitance Diode fo UHF/VHF tuner Vr 34V UFP package
33	RESISTOR	KOA	RK73B1JTDD472J	4,444	4.7KΩ 1608 5%
34	RESISTOR	KOA	RK73B1JTDD203J	5,000	20KΩ 1608 5%
35	RESISTOR	KOA	RK73B2BTDD561J	256	560Ω 3216 5%
36	RESISTOR	KOA	RK73B1JTDD302J	5,000	3KΩ 1608 5%
37	RESISTOR	KOA	RK73B1JTDD471J	5,000	470Ω 1608 5%
38	RESISTOR	KOA	RK73B1JTDD391J	5,000	390Ω 1608 5%
39	RESISTOR	KOA	RK73H1ETTP1001F	6,782	1KΩ 1005 1%
40	RESISTOR	WALSHIN	WR20X471JTL	1,884	470Ω 5025 5%
41	RESISTOR	WALSHIN	WR12X100JTL	4,990	10Ω 3216 5%
42	RESISTOR	WALSHIN	WR04X102JTL	9,589	1KΩ 1005 5%
43	RESISTOR	WALSHIN	WR06X561JTL	4,990	560Ω 1608 5%
44	RESISTOR	WALSHIN	WR06X331JTL	4,990	330Ω 1608 5%
45	RESISTOR	WALSHIN	WR04X3302FTL	3,662	33KΩ 1005 5%
46	RESISTOR	WALSHIN	WR04X2703FTL	3,636	270KΩ 1005 5%
47	RESISTOR	WALSHIN	WR04X100JTL	3,667	10Ω 100 5%
48	RESISTOR	WALSHIN	WR06X4R7 JTL	5,000	4.7Ω 1608 5%
49	RESISTOR	WALSHIN	WR06X203 JTL	5,000	20KΩ 1608 5%
50	RESISTOR	WALSHIN	WR06X6193 FTL	4,896	619KΩ 1608 1%
51	RESISTOR	WALSHIN	WR06X8062 FTL	4,898	80.6KΩ 1608 1%
52	RESISTOR	WALSHIN	WR06X1962 FTL	4,894	1.96KΩ 1608 1%
53	RESISTOR	WALSHIN	WR06X393 JTL	4,898	39KΩ 1608 5%
54	RESISTOR	WALSHIN	WR06X9763 FTL	4,898	976KΩ 1608 1%

55	RESISTOR	WALSHIN	WR06X1823 FTL	4,892	182K Ω 1608 1%
56	RESISTOR	WALSHIN	WR06X1502 FTL	4,896	15K Ω 1608 1%
57	RESISTOR	WALSHIN	WR06X302 JTL	4,898	3K Ω 1608 5%
58	RESISTOR	WALSHIN	WR06X102 JTL	4,393	1K Ω 1608 5%
59	RESISTOR	WALSHIN	WR06X7320 FTL	4,694	732 Ω 1608 1%
60	RESISTOR	WALSHIN	WR06X1002 FTL	3,985	10K Ω 1608 1%
61	RESISTOR	WALSHIN	WR12X6800FTL	5,000	680 Ω 3216 1%
62	INDUCTOR	TDK	SLF10165T-100M3R83PF	500	SLF SERIES 10165(1.01 \times 10.1 \times 6.5)10 μ H \pm 20% 3.8A
63	INDUCTOR	SUMIDA	CDRH104NP-470MC	480	47 μ H 1.1A 210 m Ω 9.8 \times 8.9 \times 5.0mm
64	CONNECTOR	JST	B5P-VH(LF)(SN)	60	HEADER VHTOP 5PIN 3.96mm
65	CONNECTOR	JST	B8P-VH(LF)(SN)	30	HEADER VHTOP 8PIN 3.96mm